REACH ROBOTICS

RA-1XXX

ALPHA ACTUATOR

HIGH TORQUE ACTUATOR

A high torque single rotate actuator for small ROVs.

LIGHTWEIGHT & COMPACT
Small footprint for easy integration

RELIABLE PERFORMANCE
Engineered for tough underwater conditions

FIELD SERVICEABLE
Quick maintenance with replaceable components

EASY TO INTEGRATE
Simple mechanical and electrical interfaces

Lift Capacity	Reach	Functions	In-Air Weight	Depth Rating
N/A	**N/A**	**1**	**0.34 kg / 0.75 lb**	**300 MSW / 980 ft**

TECHNICAL DRAWINGS





JOINT ROTATION	
A	Continuous Rotate

COMPONENT DIMENSIONS	
A	145mm
B	125mm
C	Ø40mm

END EFFECTOR OPTIONS

CUTTER JAWS
RA-1018

PARALLEL JAWS
RA-1012

QUAD JAWS
RA-1017

SOFT JAWS
RA-1048

SPECIAL RECOVERY TOOL
RA-1037

STANDARD JAWS
RA-1014

KEY FEATURES

- All-Electric.
- Designed and Tested for Harsh Environments.
- Intuitive User Interface with 3D Visualisation and Telemetry.
- Software Developer Kit (SDK) for Custom Control Applications.

MOUNTING KITS

Contact us at sales@reachrobotics.com for mounting options.

CONTROLLER OPTIONS

Contact us at sales@reachrobotics.com for control options.

ACCESSORIES

REACH ALPHA VACUUM PULLING KIT

Maintain and Monitor

REACH MICRO IP CAMERA

Smallest 300m IP Camera for Underwater Inspection

SPECIFICATIONS	REACH ALPHA 5	REACH ALPHA 3	REACH ALPHA 2	REACH ALPHA ACTUATOR
Functions	5	3	2	1
Reach	360 mm / 14.2 in	210 mm / 8.3 in	160 mm / 6.3 in	N/A
Wrist Rotation Torque	0.6 Nm / 5 lb-in	0.6 Nm / 5 lb-in	0.6 Nm / 5 lb-in	8 Nm
Wrist Rotation Speed	60° / s	60° / s	60° / s	N/A
Grab Speed	5 s	5 s	5 s	N/A
Grab Force	10 kg / 22 lb	10 kg / 22 lb	10 kg / 22 lb	N/A
Lift Capacity	2 kg / 4.4 lb	4 kg / 8.8 lb	N/A	N/A
Weight (Air)	1.36 kg / 3 lb	0.9 kg / 2 lb	0.39 kg / 0.85 lb	0.34 kg / 0.75 lb
Weight (Water)	0.9 kg / 2 lb	0.65 kg / 1.4 lb	0.24 kg / 0.5 lb	0.15 kg / 0.33 lb
Outer Diameter	40 mm / 1.6 in	40 mm / 1.6 in	40 mm / 1.6 in	40 mm / 1.6 in
Connector Cable	Teledyne 6 Pin IE55 Impulse Cable	Teledyne 6 Pin IE55 Impulse Cable	Teledyne 6 Pin IE55 Impulse Cable	Teledyne 6 Pin IE55 Impulse Cable
Control Modes	Position, Velocity, Cartesian Velocity (X, Y, Z)	Position, Velocity	Position, Velocity	Position, Velocity
Voltage	18 - 30 V	18 - 30 V	18 - 30 V	18 - 30 V
Power (Nominal)	35 W	20 W	11 W	11 W
COMS	Serial (232 / 485)	Serial (232 / 485)	Serial (232 / 485)	Serial (232 / 485)
Rated Depth	300 MSW / 980 ft	300 MSW / 980 ft	300 MSW / 980 ft	300 MSW / 980 ft
Rated Temp	5 - 35 °C / 41 - 95 °F	5 - 35 °C / 41 - 95 °F	5 - 35 °C / 41 - 95 °F	5 - 35 °C / 41 - 95 °F
Storage Temp	-10 - 80 °C / 14 - 176 °F	-10 - 80 °C / 14 - 176 °F	-10 - 80 °C / 14 - 176 °F	-10 - 80 °C / 14 - 176 °F