REACH ROBOTICS

RX-3XXX

X 3

3-FUNCTION MANIPULATOR

A next-generation manipulator system for complex remote intervention critical commercial and military operations.

LIGHTWEIGHT & COMPACT
Small footprint for easy integration

RELIABLE PERFORMANCE
Engineered for tough underwater conditions

FIELD SERVICEABLE
Quick maintenance with replaceable components

EASY TO INTEGRATE
Simple mechanical and electrical interfaces

Lift Capacity	Reach	Functions	In-Air Weight	Depth Rating
3 kg / 6.6 lb	**280 mm / 11.0 in**	**3**	**1.6 kg / 3.5 lb**	**300 MSW / 980 ft**

TECHNICAL DRAWINGS







JOINT ROTATION	
A	**Max open 75 mm**
B	**360° (continuous)**
C	**360° (continuous)**

COMPONENT DIMENSIONS	
A	**Max open 75 mm**
B	**29 mm**
C	**259 mm**
D	**136 mm**

RANGE OF MOTION		
A	**Max Envelope**	**Ø520mm**
B	**Max Reach**	**238mm**

END EFFECTOR OPTIONS

CUTTER JAWS
RX-5030

PARALLEL JAWS
RX-5020

STANDARD JAWS
RX-5010

KEY FEATURES

- All-Electric.
- 3-Functions for Precise Manipulation.
- Designed and Tested for Harsh Environments.
- Intuitive User Interface with 3D Visualisation and Telemetry.
- Software Developer Kit (SDK) for Custom Control Applications.
- Available with high force cutter attachment.

MOUNTING KITS

Contact us at sales@reachrobotics.com for mounting options.

CONTROLLER OPTIONS

Contact us at sales@reachrobotics.com for control options.

ACCESSORIES

REACH MICRO IP CAMERA

Smallest 300m IP Camera for Underwater Inspection

SPECIFICATIONS	REACH X 7 AIS	REACH X 7	REACH X 5	REACH X 3	REACH X 2	REACH X 5 AIS
Functions	7	7	5	3	2	5
Reach	470 mm / 18.5 in	470 mm / 18.5 in	390 mm / 16.2 in	280 mm / 11.0 in	190 mm / 7.5 in	365 mm / 14.4 in
Wrist Rotation Torque	6 Nm / 53 lb-in	6 Nm / 53 lb-in	6 Nm / 53 lb-in	6 Nm / 53 lb-in	6 Nm / 53 lb-in	6 Nm / 53 lb-in
Wrist Rotation Speed	140° / s	140° / s	140° / s	140° / s	140° / s	140° / s
Grab Speed	3 s	3 s	3 s	3 s	3 s	3 s
Grab Force	25 kg / 55 lb	25 kg / 55 lb	25 kg / 55 lb	25 kg / 55 lb	25 kg / 55 lb	25 kg / 55 lb
Lift Capacity	3 kg / 6.6 lb	3 kg / 6.6 lb	3 kg / 6.6 lb	3 kg / 6.6 lb	N/A	3 kg / 6.6 lb
Weight (Air)	2.9 kg / 6.4 lb	2.9 kg / 6.4 lb	2.76 kg / 6 lb	1.6 kg / 3.5 lb	0.95 kg / 2 lb	2.3 kg / 5 lb
Weight (Water)	1.8 kg / 4 lb	1.8 kg / 4 lb	1.9 kg / 4.2 lb	0.95 kg / 2 lb	0.73 kg / 1.6 lb	1.6 kg / 3.5 lb
Outer Diameter	50 mm / 2 in	50 mm / 2 in	50 mm / 2 in	50 mm / 2 in	50 mm / 2 in	50 mm / 2 in
Connector Cable	Teledyne 6 Pin IE55 Impulse Cable	Teledyne 6 Pin IE55 Impulse Cable	Teledyne 6 Pin IE55 Impulse Cable	Teledyne 6 Pin IE55 Impulse Cable	Teledyne 6 Pin IE55 Impulse Cable	Teledyne 6 Pin IE55 Impulse Cable
Control Modes	Position, Velocity, Cartesian Velocity (X, Y, Z, R, P, Y)	Position, Velocity, Cartesian Velocity (X, Y, Z, R, P, Y)	Position, Velocity, Cartesian Velocity (X, Y, Z)	Position, Velocity	Position, Velocity	Position, Velocity, Cartesian Velocity (X, Y, Z, R, P, Y)
Voltage	24 - 30V	24 - 30V	24 - 30 V	24 - 30 V	24 - 30 V	24 - 30V
Power (Nominal)	360 W	180 W	120 W	90 W	60 W	240 W
COMS	Ethernet	Serial (232 / 485) AND Ethernet	Serial (232 / 485) OR Ethernet	Serial (232 / 485) OR Ethernet	Serial (232 / 485) OR Ethernet	Ethernet
Rated Depth	300 MSW / 980 ft	300 MSW / 980 ft	300 MSW / 980 ft	300 MSW / 980 ft	300 MSW / 980 ft	300 MSW / 980 ft
Rated Temp	5 - 30 °C / 41 - 86 °F (water)	5 - 30 °C / 41 - 86 °F (water)	5 - 30 °C / 41 - 86 °F (water)	5 - 30 °C / 41 - 86 °F (water)	5 - 30 °C / 41 - 86 °F (water)	5 - 30 °C / 41 - 86 °F (water)
Storage Temp	-10 - 80 °C / 14 - 176 °F (air)	-10 - 80 °C / 14 - 176 °F (air)	-10 - 80 °C / 14 - 176 °F (air)	-10 - 80 °C / 14 - 176 °F (air)	-10 - 80 °C / 14 - 176 °F (air)	-10 - 80 °C / 14 - 176 °F (air)